Wire Mesh Sling


Product Overview

The STAS wire mesh sling is made of riveted chain links. Produced in steel, it offers a safety factor of 4. Ideal for heavy-duty applications where woven material slings are at risk of damage.

- WLL from 1.50t to 15t
- Heavy Duty, slash resistant sling
- Length made to order







| WLL direct lifting kg | WLL U shape lifting kg | A mm | B mm | C mm | L m | Mass kg | Mass per extra metre kg | REF |
|-----------------------------|------------------------------|----------------|---------|----------------|--------|-------------------|-------------------------------|---------|
| 1 500 | 3 000 | 75 | 55 | 36 | 1 | 4,0 | 2,3 | WMS150 |
| 2 000 | 4 000 | 90 | 60 | 46 | 2 | 8,0 | 3,1 | WMS200 |
| 3 000 | 6 000 | 105 | 70 | 45 | 2 | 19,0 | 4,6 | WMS300 |
| 4 000 | 8 000 | 120 | 80 | 55 | 3 | 23,0 | 6,0 | WMS400 |
| 5 000 | 10 000 | 120 | 80 | 70 | 3 | 27,0 | 7,4 | WMS500 |
| 7 500 | 15 000 | 150 | 100 | 105 | 3 | 43,0 | 11,0 | WMS750 |
| 10 000 | 20 000 | 180 | 120 | 140 | 4 | 70,0 | 14,0 | WMS1000 |
| 12 500 | 25 000 | 200 | 135 | 175 | 4 | 89,0 | 15,0 | WMS1250 |
| 15 000 | 30 000 | 225 | 150 | 210 | 4 | 108,0 | 18,0 | WMS1500 |

